

Flexible Feeder™ Connector ACC-15BAFFT10U

Features:

- F Female to TX15 Flexible Feeder™ Adapter
- Semiflex / Hardline Product Group
- 3 - Piece
- Truly Non-Rotational Design
- Positive Stop Installation
- SCTE Compliant
- Inner Conductor Trim Guide



ACC-15BAFFT10U

Connector Ordering Information:

Description	Part Number
TX15 Flexible Feeder™ CATV F Female Connector	ACC-15BAFFT10U

Product Specifications:

Material	Detail
Connector Body	Aluminum – 6262 Alloy
Interface Contacts	Brass- Alloys QQQ-B-626
Insulators	Thermally Stable Plastics
O Rings	Ethylene Propylene
Environmental	
Operating Temperature	-40° C to + 60° C
Corrosion, Minimum	Bellcore GR-2846-CORE, ATM B117 – 336 hours
Mechanical	
Mating	Standard 5/8-24 UNEF and 3/8-32 Threads
Cable Retention, lbf (N)	250, (1,112)

Dimensions:

	inches	mm
Connector Body	3.140	79.76
Connector Diameter	1.090	27.69
Hex Size, Major	1.000	25.40
Adapter Body, Length	1.450	36.83
F Female, Length	0.320	8.13
Total Thread	1.000	25.40
Hex Size, Minor	0.750	19.0
Total Adapter, Length	4.590	116.59

Cable Prep Dimensions:

	inches	mm
Inner Conductor Length	1.000	25.40
Outer Jacket Trim Length	0.250	6.35

Electrical Specifications:

Impedance	75 ∇ 2 Ω
Return Loss @ 1 GHz	- 20 dB min
Insertion Loss @ 1 GHz	0.20 dB max