


# ABS Coaxial Cable Product Type: T11TQP77-V (CATV) Black

Series 11 Coaxial Cable
Copper Clad Steel Conductor
Foamed Polyethylene Dielectric
Bonded APA Laminate Shield
77% Aluminum Braid
APA Laminate Shield (QuickPrep)
Black PVC Jacket
NEC 820 CATV Listed



Cable Ordering Information

| Part Number          | Description                | NEC / CSA Listing |  |
|----------------------|----------------------------|-------------------|--|
| 011E77V04BK0010000R1 | T11TQP77-V (CATV)<br>Black | NEC 820 CATV      |  |
|                      |                            |                   |  |

### Characteristics

| Material                        | Detail                      | inches      | mm       |
|---------------------------------|-----------------------------|-------------|----------|
| Inner Conductor                 | Copper Clad Steel           | 0.0641      | 1.63     |
| Dielectric                      | Foamed Polyethylene         | 0.280       | 7.11     |
| 1st Outer Conductor             | Sealed APA Tape             | 0.288       | 7.32     |
| 2 <sup>nd</sup> Outer Conductor | 77% Aluminum Braid          | 0.312       | 7.92     |
| 3 <sup>rd</sup> Outer Conductor | APA Tape (QuickPrep)        |             |          |
| Floodant                        |                             |             |          |
| Jacket                          | PVC, Flame Retardant, Black | 0.400       | 10.2     |
| Twisted Pairs                   |                             |             |          |
| Messenger                       |                             |             |          |
| Mechanical Specifications       |                             |             |          |
| Minimum Bend Radius, in. (mm)   |                             | 1.5         | ( 38.10) |
| Product Weight                  | (less reel)                 | 58 lbs /kft |          |

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t11tqp77-v (catv) black\_1.8ghz18.docx

Revision: 12.19.2018 Page: 1 of 2

### uncontrolled copy

All Rights Reserved,

Specifications subject to change without notice

Amphenol Broadband Solutions

358 Hall Avenue Wallingford, CT 06492 Toll Free +1-800-677-2288 Toll +1-434-432-1800 Fax +1-434-432-1821

www.timesfiber.com



# ABS Coaxial Cable Product Type: T11TQP77-V (CATV) Black

| Electrical Specifications  |                |           |  |  |  |
|----------------------------|----------------|-----------|--|--|--|
| Impedance, $\Omega$        | 75 ± 3         |           |  |  |  |
| Velocity of Propagation, % | 85             |           |  |  |  |
| Capacitance, Nominal       | 16.2 pF/ft     | 53.2 pF/m |  |  |  |
| DC Resistance              | $\Omega$ / kft | Ω/km      |  |  |  |
| Inner Conductor            | 12.3           | 40        |  |  |  |
| Outer Conductor            | 4.24           | 14        |  |  |  |
| Loop                       | 16.5           | 54        |  |  |  |

| Attenuation, Maximum @ 68 °F (20 °C) |             |            |  |  |  |
|--------------------------------------|-------------|------------|--|--|--|
| Frequency, MHz                       | dB / 100 ft | dB / 100 m |  |  |  |
| 5                                    | 0.38        | 1.25       |  |  |  |
| 55                                   | 0.96        | 3.15       |  |  |  |
| 211                                  | 1.90        | 6.23       |  |  |  |
| 250                                  | 2.05        | 6.73       |  |  |  |
| 270                                  | 2.13        | 6.99       |  |  |  |
| 300                                  | 2.25        | 7.38       |  |  |  |
| 330                                  | 2.35        | 7.71       |  |  |  |
| 350                                  | 2.42        | 7.94       |  |  |  |
| 400                                  | 2.60        | 8.53       |  |  |  |
| 450                                  | 2.75        | 9.02       |  |  |  |
| 500                                  | 2.90        | 9.51       |  |  |  |
| 550                                  | 3.04        | 9.97       |  |  |  |
| 600                                  | 3.18        | 10.43      |  |  |  |
| 750                                  | 3.65        | 11.98      |  |  |  |
| 870                                  | 4.06        | 13.32      |  |  |  |
| 1000                                 | 4.35        | 14.27      |  |  |  |
| 1100                                 | 4.54        | 14.90      |  |  |  |
| 1200                                 | 4.71        | 15.45      |  |  |  |
| 1218                                 | 4.92        | 16.14      |  |  |  |
| 1300                                 | 4.96        | 16.27      |  |  |  |
| 1400                                 | 5.14        | 16.86      |  |  |  |
| 1500                                 | 5.45        | 17.88      |  |  |  |
| 1600                                 | 5.66        | 18.57      |  |  |  |
| 1700                                 | 5.86        | 19.23      |  |  |  |
| 1794                                 | 5.99        | 19.65      |  |  |  |
| 1800                                 | 6.04        | 19.82      |  |  |  |

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: t11tqp77-v (catv) black\_1.8ghz18.docx

Revision: 12.19.2018 Page: 2 of 2

#### uncontrolled copy

All Rights Reserved,

Specifications subject to change without notice

Amphenol Broadband Solutions 358 Hall Avenue

Wallingford, CT 06492
Toll Free +1-800-677-2288
Toll +1-434-432-1800
Fax +1-434-432-1821
www.timesfiber.com